

JAN-15-2007 MON 17:50

FAX NO.

RECEIVED
CENTRAL FAX CENTER

JAN 15 2007

P. 07/21

Customer No.: 31561
Application No.: 10/711,880
Docket NO.: 13944-US-PA

Claim 7 (original) The projection device of claim 2, wherein the beam breaking part is disposed between the projection lens and the screen.

Claim 8 (original) The projection device of claim 1, further comprising a control unit, to synchronously control the color production device, the light valve, and the beam breaker module.

Claim 9 (original) The projection device of claim 2, further comprising a control unit, wherein the control unit comprises:

a light valve driver, electrically coupled with the light valve;

an actuator driver, electrically coupled with the actuator to control the beam breaking part; and

a color production device driver, electrically coupled with the color production device,

wherein the light valve driver, the actuator driver, and the color production device driver are used to synchronously control the light valve, the beam breaker module, and the color production device.

Claim 10 (original) The projection device of claim 1, wherein the color production device comprises a color wheel.

Claim 11 (currently amended) The projection device of claim 10, wherein the

Page 4 of 18

CFC received 15 pages
missing 6 pages

Customer No.: 31561
Application No.: 10/711,880
Docket NO.: 13944-US-PA

filtering regions of the color production device~~color wheel~~ has a red filtering region, a green filtering region, and a blue filtering region.

Claim 12 (currently amended) The projection device of claim 10, wherein the filtering region of the color production device~~color wheel~~ has a red filtering region, a green filtering region, a blue filtering region, and a white filtering region.

Claim 13 (original) The projection device of claim 1, wherein the color production device comprises a color drum.

Claim 14 (currently amended) The projection device of claim 13, wherein the filtering region of the color production device~~color drum~~ has a red filtering region, a green filtering region, and a blue filtering region.

Claim 15 (currently amended) The projection device of claim 13, wherein the filtering regions of the color production device~~color wheel~~ has a red filtering region, a green filtering region, a blue filtering region, and a white filtering region.

Claim 16 (currently amended) A projection device having single light valve, having a first operation mode and a second operation mode, suitable for projecting an image to a screen, the projection device comprising:

a light source, for providing a light beam;

Customer No.: 31561
Application No.: 10/711,880
Docket NO.: 13944-US-PA

a projection lens, disposed behind the light source, and located on a propagation path of the light beam;

an image unit, disposed between the light source and the projection lens, and located on the propagation path of the light beam, wherein the image unit comprises a color production device and a light valve disposed behind the color production device, and located on the propagation path of the light beam, wherein the color production device comprises a plurality of filtering regions corresponding to a plurality of color lights of the light beam, and each region being on the propagation path indicates a state of the color production device; and

a beam breaker module, disposed between the light source and the screen, the beam breaker comprising an optical sensor disposed beside the color production device, so as to sense ~~[[a]]~~ the state of the color production device, wherein when the projection device is at the first operation mode, the beam breaker module cuts in the propagation path of the light beam to break the passing light beam passing through a part of the filtering regions~~within a specific time period~~, and when the projection device is at the second operation mode, the beam breaker module cuts out from the propagation path of the light beam passing through the other part of the filtering regions to project to the screen by the projection lens.

Claim 17 (previously presented) The projection device of claim 16, wherein the beam breaker module further comprises:

a beam breaking part, disposed between the light source and the screen; and

Customer No.: 31561
Application No.: 10/711,880
Docket NO.: 13944-US-PA

an actuator, coupled with the beam breaking part, so as to control the beam breaking part to cut in or cut out from the propagation path of the light beam.

Claim 18 (original) The projection device of claim 16, wherein the first operation mode is a high color saturation mode and the second operation mode is a high brightness mode.

Claim 19 (new) The projection device of claim 1, wherein the filtering regions comprises a white filtering region or an interfacing region between two of the filtering regions, and the beam breaker module blocks the light beam passing through a white filtering region or an interfacing region between two of the filtering regions.

Claim 20 (new) The projection device of claim 16, wherein the filtering regions comprises a white filtering region or an interfacing region between two of the filtering regions, and the beam breaker module blocks the light beam passing through the white filtering region or the interfacing region between two of the filtering regions.